

Naaldhulslager 12MKM1810-JTEKT - 12MKM1810-JTEKT

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/12mkm1810-jtekt>

Drawn cup needle roller bearings 



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds (min ⁻¹)		Bearing No. ²⁾	
F_w	D	C	b min.	C_0	C_{0r}	Oil lub.		Caged type	
12	18	10	8.4	4.80	4.80	27 000		With open ends	With closed end
									12MKM1810

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (φ6)		Housing bore dia. (N7)		With open ends	With closed end
		min.	max.	min.	max.		
—	—	11.989	12.000	17.977	17.995	7.2	8.2

PRODUCTKENMERKEN

Merk	JTEKT
N° Ean13	3663952469676
Binnendiameter	12 mm
Buitendiameter	18 mm
Dikte	10 mm
Gewicht	8.2 g
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE