

Naaldhulslager 15BTM2122-JTEKT - 15BTM2122-JTEKT

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/15btm2122-jtekt>

Drawn cup needle roller bearings 



Boundary dimensions (mm)			Basic load ratings (kN)		Limiting speeds (min ⁻¹)		Bearing No. ²⁾	
F_w	D	C	b min.	C_0	C_{0r}	Oil lub.	Caged type	
							With open ends	With closed end
15	21	22	—	13.0	19.5	23 000	15BTM2122	

Full complement type		Recommended dimensions (mm)				Refer. Mass (g)	
With open ends	With closed end	Shaft dia. (f6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	14.989	15.000	20.991 ⁽⁴⁾	21.012 ⁽⁴⁾	20	—

PRODUCTKENMERKEN

Merk	JTEKT
N° Ean13	3663952470177
Binnendiameter	15 mm
Buitendiameter	21 mm
Dikte	22 mm
Gewicht	20 g
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE