

## Naaldhulslager BHTM1616A-JTEKT - BHTM1616A-JTEKT

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/bhtm1616a-jtekt>

Drawn cup needle roller bearings 



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	Bearing No. <sup>2)</sup>
$F_w$	$D$	$C$	$b$ min.	$C_0$	$C_{0r}$	Oil lub.	Caged type With open ends    With closed end
16	24	16	13.3	12.2	14.9	21 000	<b>BHTM1616A</b>

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (H6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	15.989	16.000	23.991 <sup>4)</sup>	24.012 <sup>4)</sup>	20	23

## PRODUCTKENMERKEN

Merk	JTEKT
N° Ean13	3663952470368
Binnendiameter	16 mm
Buitendiameter	24 mm
Dikte	16 mm
Gewicht	20 g
Verpakking	1

[contact@123kogellager.nl](mailto:contact@123kogellager.nl)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE