

Naaldhulslager 17BKM2517-JBUUH-JTEKT - 17BKM2517-JBUUH-JTEKT

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/17bkm2517-jbuuh-jtekt>

Drawn cup needle roller bearings 



Boundary dimensions (mm)			Basic load ratings (kN)		Limiting speeds (min ⁻¹)		Bearing No. ²⁾	
F_w	D	C	b min.	C_0	C_{10}	Oil lub.	Caged type	
							With open ends	With closed end
17	25	16.70	—	7.30	7.90	11 000 ¹⁾	17BKM2517JBUUH	

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. ($\phi 6$) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	16.989	17.000	24.972	24.993	20	—

PRODUCTKENMERKEN

Merk	JTEKT
N° Ean13	3616060465306
Binnendiameter	17 mm
Buitendiameter	25 mm
Dikte	16.7 mm
Gewicht	20 g
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE