


Naaldhulslager BTM1815-JTEKT - BTM1815-JTEKT

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/btm1815-jtekt>

Drawn cup needle roller bearings 



| Boundary dimensions (mm) | | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | | Bearing No. ²⁾ | |
|--------------------------|-----|-----|----------|-------------------------|----------|--------------------------------------|----------------|---------------------------|--|
| F_w | D | C | b min. | C_0 | C_{0r} | Oil lub. | Caged type | | |
| | | | | | | | With open ends | With closed end | |
| 18 | 25 | 15 | — | 10.4 | 9.25 | 19 000 | BTM1815 | | |

| Full complement type | | Recommended dimensions (mm) | | | | Refer. Mass (g) | |
|----------------------|-----------------|-----------------------------|--------|------------------------|--------|-----------------|-----------------|
| With open ends | With closed end | Shaft dia. (d6) | | Housing bore dia. (N7) | | With open ends | With closed end |
| | | min. | max. | min. | max. | | |
| — | — | 17.989 | 18.000 | 24.972 | 24.993 | 18 | — |

PRODUCTKENMERKEN

| | |
|----------------|---------------|
| Merk | JTEKT |
| N° Ean13 | 3663952470689 |
| Binnendiameter | 18 mm |
| Binnendiameter | 0.709" inch |
| Buitendiameter | 25 mm |
| Buitendiameter | 0.984" inch |
| Dikte | 15 mm |
| Dikte | 0.591" inch |
| Gewicht | 18 g |
| Verpakking | 1 |

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE