

## Naaldhulslager BHTM1920-JTEKT - BHTM1920-JTEKT

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/bhtm1920-jtekt>

Drawn cup needle roller bearings 



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	Bearing No. <sup>2)</sup>
$F_w$	$D$	$C$	$b$ min.	$C_0$	$C_{0r}$	Oil lub.	Caged type With open ends    With closed end
19	27	20	—	17.0	23.4	18 000	<b>BHTM1920</b>

Full complement type		Recommended dimensions (mm)				Refer. Mass (g)	
With open ends	With closed end	Shaft dia. (φ6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	18.987	19.000	26.972	26.993	30	—

### PRODUCTKENMERKEN

Merk	JTEKT
N° Ean13	3663952470740
Binnendiameter	19 mm
Buitendiameter	27 mm
Dikte	20 mm
Gewicht	30 g
Verpakking	1

[contact@123kogellager.nl](mailto:contact@123kogellager.nl)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE