

## Naaldhulslager 20BTM2820A-JTEKT - 20BTM2820A-JTEKT

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/20btm2820a-jtekt>

Drawn cup needle roller bearings 



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	Bearing No. <sup>2)</sup>
$F_w$	$D$	$C$	$b$ min.	$C_0$	$C_{0r}$	Oil lub.	Caged type With open ends    With closed end
4	28	20	—	17.4	22.3	17 000	20BTM2820A

Full complement type		Recommended dimensions (mm)				Refer. Mass (g)	
With open ends	With closed end	Shaft dia. (d6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	19.987	20.000	27.991 <sup>(4)</sup>	28.012 <sup>(4)</sup>	31	—

## PRODUCTKENMERKEN

Merk	JTEKT
N° Ean13	3663952471037
Binnendiameter	20 mm
Buitendiameter	28 mm
Dikte	20 mm
Gewicht	31 g
Verpakking	1

[contact@123kogellager.nl](mailto:contact@123kogellager.nl)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE