


Naaldhulslager 22MM2820-JTEKT - 22MM2820-JTEKT

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/22mm2820-jtekt>

Drawn cup needle roller bearings 

Full complement type
With closed end



| Boundary dimensions (mm) | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | Bearing No. ²⁾ |
|--------------------------|-----|-----|-------------------------|-------|--------------------------------------|---------------------------|
| F_w | D | C | b min. | C_0 | C_{0r} | Oil lub. |
| 22 | 28 | 20 | 17.2 | 20.3 | 47.2 | 5 800 |

| Full complement type | | Recommended dimensions (mm) | | | | (Refer.) Mass (g) | |
|----------------------|-----------------|-----------------------------|--------|--------------------------------|--------|-------------------|-----------------|
| With open ends | With closed end | Shaft dia. (H6) min. | max. | Housing bore dia. (N7) min. | max. | With open ends | With closed end |
| | 22MM2820 | 21.987 | 22.000 | 27.972 | 27.993 | 29 | 32 |

PRODUCTKENMERKEN

| | |
|----------------|---------------|
| Merk | JTEKT |
| N° Ean13 | 3663952471143 |
| Binnendiameter | 22 mm |
| Buitendiameter | 28 mm |
| Dikte | 20 mm |
| Gewicht | 32 g |
| Verpakking | 1 |

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE