

Naaldhulslager BM2526-JTEKT - BM2526-JTEKT

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/bm2526-jtekt>

Drawn cup needle roller bearings Koyo

Full complement type
With open ends

BM, BH-M

| Boundary dimensions (mm) | | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | Bearing No. ²⁾ | |
|--------------------------|-----|-----|-------------|-------------------------|----------|--------------------------------------|---------------------------|-----------------|
| F_w | D | C | b min. | C_0 | C_{0r} | Oil lub. | Caged type | |
| | | | | | | | With open ends | With closed end |
| 25 | 32 | 26 | — | 30.9 | 72.4 | 5 100 | | |

| Full complement type | | | | Recommended dimensions (mm) | | | | (Refer.) Mass (g) | |
|----------------------|--|-----------------|--|-----------------------------|--------|------------------------|--------|-------------------|-----------------|
| With open ends | | With closed end | | Shaft dia. (H6) | | Housing bore dia. (H7) | | With open ends | With closed end |
| | | | | min. | max. | min. | max. | | |
| BM2526 | | | | 24.987 | 25.000 | 31.967 | 31.992 | 48 | — |

PRODUCTKENMERKEN

| | |
|----------------|---------------|
| Merk | JTEKT |
| N° Ean13 | 4549250003547 |
| Binnendiameter | 25 mm |
| Buitendiameter | 32 mm |
| Dikte | 26 mm |
| Gewicht | 48 g |
| Verpakking | 1 |

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE