

## Naaldhulslager BHTM2510A-JTEKT - BHTM2510A-JTEKT

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/bhtm2510a-jtekt>

Drawn cup needle roller bearings 



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	Bearing No. <sup>2)</sup>
$F_w$	$D$	$C$	$b$ min.	$C_0$	$C_{0r}$	Oil lub.	Caged type With open ends With closed end
25	33	10	—	8.90	10.3	14 000	BHTM2510A

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (φ6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	24.987	25.000	32.989 <sup>(4)</sup>	33.014 <sup>(4)</sup>	18	—

### PRODUCTKENMERKEN

Merk	JTEKT
N° Ean13	3663952471433
Binnendiameter	25 mm
Binnendiameter	0.984" inch
Buitendiameter	33 mm
Buitendiameter	1.299" inch
Dikte	10 mm
Dikte	0.394" inch
Gewicht	18 g
Verpakking	1

[contact@123kogellager.nl](mailto:contact@123kogellager.nl)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE