

Naaldhulslager MHKM2530-JTEKT - MHKM2530-JTEKT

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/mhkm2530-jtekt>

Drawn cup needle roller bearings Koyo



Boundary dimensions (mm)			Basic load ratings (kN)		Limiting speeds (min ⁻¹)	Bearing No. ²⁾
F_w	D	C	b min.	C_{10}	Oil lub.	Caged type With open ends With closed end
25	33	30	27.3	27.7	47.4	14 000 MHKM2530

Full complement type		Recommended dimensions (mm)				Refer. Mass (g)	
With open ends	With closed end	Shaft dia. (H6) min.	max.	Housing bore dia. (H7) min.	max.	With open ends	With closed end
—	—	24.987	25.000	32.967	32.992	54	61

PRODUCTKENMERKEN

Merk	JTEKT
N° Ean13	3663952471525
Binnendiameter	25 mm
Binnendiameter	0.984" inch
Buitendiameter	33 mm
Buitendiameter	1.299" inch
Dikte	30 mm
Dikte	1.181" inch
Gewicht	61 g
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE