


## Naaldhulslager MHKM3030-JTEKT - MHKM3030-JTEKT

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/mhkm3030-jtekt>

Drawn cup needle roller bearings Koyo



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	Bearing No. <sup>2)</sup>
$F_w$	$D$	$C$	$b$ min.	$C_r$	$C_{0r}$	Oil lub.	Caged type With open ends With closed end
30	40	30	27.3	35.3	58.8	12 000	MHKM3030

Full complement type		Recommended dimensions (mm)				Refer. Mass (g)	
With open ends	With closed end	Shaft dia. (H6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	29.987	30.000	39.967	39.992	83	94

## PRODUCTKENMERKEN

Merk	JTEKT
N° Ean13	3663952472003
Binnendiameter	30 mm
Buitendiameter	40 mm
Dikte	30 mm
Gewicht	94 g
Verpakking	1

[contact@123kogellager.nl](mailto:contact@123kogellager.nl)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE