

## Naaldhulslager BHTM3515-JTEKT - BHTM3515-JTEKT

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/bhtm3515-jtekt>

Drawn cup needle roller bearings 



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	Bearing No. <sup>2)</sup>
$F_w$	$D$	$C$	$b$ min.	$C_r$	$C_{0r}$	Oil lub.	Caged type With open ends With closed end
35	45	15	—	18.4	26.6	10 000	<b>BHTM3515</b>

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (φ6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	34.984	35.000	44.967	44.992	47	—

## PRODUCTKENMERKEN

Merk	JTEKT
N° Ean13	3616060465399
Binnendiameter	35 mm
Buitendiameter	45 mm
Dikte	15 mm
Gewicht	47 g
Verpakking	1

[contact@123kogellager.nl](mailto:contact@123kogellager.nl)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE