


## Naaldhulslager MHKM3520-JTEKT - MHKM3520-JTEKT

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/mhkm3520-jtekt>

Drawn cup needle roller bearings 



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	Bearing No. <sup>2)</sup>
$F_w$	$D$	$C$	$b$ min.	$C_0$	$C_{0r}$	Oil lub.	Caged type With open ends With closed end
35	45	20	17.3	26.0	41.7	10 000	MHKM3520

Full complement type		Recommended dimensions (mm)				Refer. Mass (g)	
With open ends	With closed end	Shaft dia. (H6) min.	max.	Housing bore dia. (H7) min.	max.	With open ends	With closed end
—	—	34.984	35.000	44.967	44.992	64	72

## PRODUCTKENMERKEN

Merk	JTEKT
N° Ean13	3663952472324
Binnendiameter	35 mm
Buitendiameter	45 mm
Dikte	20 mm
Gewicht	72 g
Verpakking	1

[contact@123kogellager.nl](mailto:contact@123kogellager.nl)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE