


## Naaldhulslager MKM3820-JTEKT - MKM3820-JTEKT

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/mkm3820-jtekt>

Drawn cup needle roller bearings Koyo



| Boundary dimensions (mm) |     |     |             | Basic load ratings (kN) |          | Limiting speeds (min <sup>-1</sup> ) | Bearing No. <sup>2)</sup>                    |
|--------------------------|-----|-----|-------------|-------------------------|----------|--------------------------------------|--|
| $F_w$                    | $D$ | $C$ | $b$<br>min. | $C_r$                   | $C_{0r}$ | Oil lub.                             | Caged type<br>With open ends With closed end |
| 38                       | 48  | 20  | 17.3        | 27.1                    | 44.5     | 9 500                                | MKM3820                                      |

| Full complement type |                 | Recommended dimensions (mm) |        |                                |        | (Refer.) Mass (g) |                 |
|----------------------|-----------------|-----------------------------|--------|--------------------------------|--------|-------------------|-----------------|
| With open ends       | With closed end | Shaft dia. (φ6)<br>min.     | max.   | Housing bore dia. (N7)<br>min. | max.   | With open ends    | With closed end |
| —                    | —               | 37.984                      | 38.000 | 47.967                         | 47.992 | 67                | 76              |

## PRODUCTKENMERKEN

|                |               |
|----------------|---------------|
| Merk           | JTEKT         |
| N° Ean13       | 3663952472454 |
| Binnendiameter | 38 mm         |
| Buitendiameter | 48 mm         |
| Dikte          | 20 mm         |
| Gewicht        | 76 g          |
| Verpakking     | 1             |

[contact@123kogellager.nl](mailto:contact@123kogellager.nl)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE