


## Naaldhulslager 50BTM5820J-JTEKT - 50BTM5820J-JTEKT

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/50btm5820j-jtekt>

Drawn cup needle roller bearings 



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	Bearing No. <sup>2)</sup>
$F_w$	$D$	$C$	$b$ min.	$C_0$	$C_{0r}$	Oil lub.	Caged type With open ends    With closed end
50	58	20	17.3	28.4	61.0	7 500	50BTM5820J

Full complement type		Recommended dimensions (mm)				Refer. Mass (g)	
With open ends	With closed end	Shaft dia. (d6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	49.984	50.000	57.961	57.991	68	76

## PRODUCTKENMERKEN

Merk	JTEKT
N° Ean13	3663952472881
Binnendiameter	50 mm
Buitendiameter	58 mm
Dikte	20 mm
Gewicht	68 g
Verpakking	1

[contact@123kogellager.nl](mailto:contact@123kogellager.nl)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE