

## Naaldhulslager NQ18-20-JTEKT - NQ18-20-JTEKT

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/nq18-20-jtekt>

### Machined ring needle roller bearings Koyo

$F_w$  29 ~ 37 mm

Without inner ring



Boundary dimensions (mm)				Basic load ratings (kN)			Limiting speeds <sup>1)</sup> (min <sup>-1</sup> )		Bearing No.
$F_w$	$d$	$D$	$B$	$C_r$	$C_{10}$	Oil lub.		Without inner ring	
18	—	26	20	0.5	14.1	21.7	25 000	<b>NQ18/20</b>	
		Mounting dimensions (mm)			[Refer.] Mass (kg)		[Refer.] Applicable inner ring No.		
		$d_a$	$D_a$	$r_a$	Without inner ring	With inner ring			
		max.	max.	max.	—	—			
		—	24	0.3	0.035	—			

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.  
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

## PRODUCTKENMERKEN

Merk	JTEKT
N° Ean13	3663952477367
Binnendiameter	18 mm
Buitendiameter	26 mm
Dikte	20 mm
Gewicht	35 g
Verpakking	1

[contact@123kogellager.nl](mailto:contact@123kogellager.nl)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE