

# Naaldhulslager 20NQ3315D-JTEKT - 20NQ3315D-JTEKT

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/20nq3315d-jtekt>

Machined ring needle roller bearings ————— **Koyo**  
F<sub>W</sub> 29 ~ 37 mm

Without inner ring



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds <sup>1)</sup> (min <sup>-1</sup> )		Bearing No.
F <sub>w</sub>	d	D	B	C <sub>r</sub>	C <sub>0r</sub>	Oil lub.	Without inner ring	
20	—	33	15	14.0	16.9	21 000	<b>20NQ3315D</b>	
Mounting dimensions (mm)				(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.		
With inner ring				d <sub>i</sub> min.	D <sub>i</sub> max.	r <sub>a</sub> max.	Without inner ring	With inner ring
				—	29	0.6	0.052	—

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.  
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

## PRODUCTKENMERKEN

Merk	JTEKT
N° Ean13	3663952477473
Binnendiameter	20 mm
Buitendiameter	33 mm
Dikte	15 mm
Gewicht	52 g
Verpakking	1

[contact@123kogellager.nl](mailto:contact@123kogellager.nl)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE