

Naaldhulslager NQ22-20-JTEKT - NQ22-20-JTEKT

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/nq22-20-jtekt>

Machined ring needle roller bearings Koyo

F_w 29 ~ 37 mm

Without inner ring



Boundary dimensions (mm)				Basic load ratings (kN)			Limiting speeds ¹⁾ (min ⁻¹)		Bearing No.
F_w	d	D	B	C_r	C_{10}	Oil lub.	Grease lub.	Without inner ring	
22	—	30	20	15.3	25.6	21 000	—	NQ22/20	
		Mounting dimensions (mm)			Weight (kg)		Applicable inner ring No.		
		d_a	D_a	r_a	Without inner ring	With inner ring			
		max.	max.	max.	—	—			
		—	28	0.3	0.040	—			

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

PRODUCTKENMERKEN

Merk	JTEKT
N° Ean13	3663952477534
Binnendiameter	22 mm
Buitendiameter	30 mm
Dikte	20 mm
Gewicht	40 g
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE