

# Naaldhulslager 12NQ2410A-JTEKT - 12NQ2410A-JTEKT

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/12nq2410a-jtekt>

Machined ring needle roller bearings ————— **Koyo**  
F<sub>W</sub> 29 ~ 37 mm

Without inner ring



Boundary dimensions (mm)				Basic load ratings (kN)			Limiting speeds <sup>1)</sup> (min <sup>-1</sup> )		Bearing No.
F <sub>w</sub>	d	D	B	C <sub>r</sub>	C <sub>0r</sub>	Oil lub.		Without inner ring	
12	—	24	9.8	—	5.9	6.3	35 000	<b>12NQ2410A</b>	
		Mounting dimensions (mm)			(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.		
		d <sub>1</sub>	D <sub>1</sub>	r <sub>1</sub>	Without inner ring	With inner ring			
		—	22	0.3	0.023	—			

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.  
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

## PRODUCTKENMERKEN

Merk	JTEKT
N° Ean13	4549250086960
Binnendiameter	12 mm
Binnendiameter	0.472" inch
Buitendiameter	24 mm
Buitendiameter	0.945" inch
Dikte	9.8 mm
Dikte	0.386" inch
Gewicht	23 g
Verpakking	1

[contact@123kogellager.nl](mailto:contact@123kogellager.nl)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE