

# Naaldhulslager NQ152512-JTEKT - NQ152512-JTEKT

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/nq152512-jtekt>

Machined ring needle roller bearings ————— **Koyo**  
F<sub>W</sub> 29 ~ 37 mm

Without inner ring



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds <sup>1)</sup> (min <sup>-1</sup> )		Bearing No.
F <sub>w</sub>	d	D	B	C <sub>r</sub>	C <sub>0r</sub>	Oil lub.	Without inner ring	
15	—	25	12	10.5	10.8	28 000	<b>NQ152512</b>	
Mounting dimensions (mm)				(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.		
With inner ring				d <sub>1</sub> min.	D <sub>1</sub> max.	r <sub>a</sub> max.	Without inner ring	With inner ring
				—	21	0.8	0.022	—

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.  
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

## PRODUCTKENMERKEN

Merk	JTEKT
N° Ean13	3663952477602
Binnendiameter	15 mm
Buitendiameter	25 mm
Dikte	12 mm
Gewicht	22 g
Verpakking	1

[contact@123kogellager.nl](mailto:contact@123kogellager.nl)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE