

Naaldhulslager NQ16-20-JTEKT - NQ16-20-JTEKT

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/nq16-20-jtekt>

Machined ring needle roller bearings **Koyo**
F_W 29 ~ 37 mm

Without inner ring



Boundary dimensions (mm)				Basic load ratings (kN)			Limiting speeds ¹⁾ (min ⁻¹)		Bearing No.
F _w	d	D	B	C _r	C _{0r}	Oil lub.	Grease lub.	Without inner ring	
16	—	24	20	0.3	13.1	19.1	28 000	NQ16/20	
		Mounting dimensions (mm)			Weight (kg)		Applicable inner ring No.		
		d ₂	D ₂	r ₂	Without inner ring	With inner ring			
		—	22	0.3	0.032	—			

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

PRODUCTKENMERKEN

Merk	JTEKT
N° Ean13	3663952477701
Binnendiameter	16 mm
Buitendiameter	24 mm
Dikte	20 mm
Gewicht	32 g
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE