

# Naaldhulslager 17NQ3216D-JTEKT - 17NQ3216D-JTEKT

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/17nq3216d-jtekt>

Machined ring needle roller bearings Koyo  
F<sub>W</sub> 29 ~ 37 mm

Without inner ring



Boundary dimensions (mm)				Basic load ratings (kN)			Limiting speeds <sup>1)</sup> (min <sup>-1</sup> )		Bearing No.
F <sub>w</sub>	d	D	B	C <sub>r</sub>	C <sub>10</sub>	C <sub>10r</sub>	Oil lub.	Without inner ring	
17	—	32	16	—	18.0	16.5	23 000	<b>17NQ3216D</b>	
		Mounting dimensions (mm)			Weight Mass (kg)		Applicable inner ring No.		
		d <sub>1</sub>	D <sub>1</sub>	r <sub>1</sub>	Without inner ring	With inner ring			
		max.	max.	max.	—	—			
		—	28	0.6	0.053	—			

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.  
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

## PRODUCTKENMERKEN

Merk	JTEKT
N° Ean13	3663952477749
Binnendiameter	17 mm
Buitendiameter	32 mm
Dikte	16 mm
Gewicht	53 g
Verpakking	1

[contact@123kogellager.nl](mailto:contact@123kogellager.nl)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE