


Naaldhulslager MTM2520M-JTEKT - MTM2520M-JTEKT

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/mtm2520m-jtekt>

Drawn cup needle roller bearings Koyo



Boundary dimensions (mm)			Basic load ratings (kN)		Limiting speeds (min ⁻¹)		Bearing No. ²⁾	
F_w	D	C	b min.	C_0	C_{0r}	Oil lub.	Caged type	
			With open ends			With open ends		With closed end
4	32	20	—	19.1	32.5	14 000	MTM2520M	

Full complement type		Recommended dimensions (mm)				Refer. Mass (g)	
With open ends	With closed end	Shaft dia. (φ6)		Housing bore dia. (N7)		With open ends	With closed end
		min.	max.	min.	max.		
—	—	24.987	25.000	31.967	31.992	33	—

PRODUCTKENMERKEN

Merk	JTEKT
N° Ean13	4549250025457
Binnendiameter	25 mm
Buitendiameter	32 mm
Dikte	20 mm
Grenstoerental	14000 rpm
Gewicht	33 g
Dynamische belasting	19.1 kN
Statische belasting	32.5 kN
Verpakking	1
Standaard	Geen standaard

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE