


## Naaldhulslager NQIS25-22-JTEKT - NQIS25-22-JTEKT

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/nqis25-22-jtekt>

Machined ring needle roller bearings Koyo  
 $F_w$  29 ~ 37 mm

With inner ring



Boundary dimensions (mm)				Basic load ratings (kN)			Limiting speeds <sup>1)</sup> (min <sup>-1</sup> )		Bearing No.	
$F_w$	d	D	B	$C_r$	$C_{10}$	Oil lub.	Without inner ring			
32	25	47	22	0.3	31.2	41.4	14 000		—	
Mounting dimensions (mm)				(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.				
With inner ring				Without inner ring	With inner ring					
NQIS25/22				27	45	0.3	0.123	0.167	—	

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.  
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

### PRODUCTKENMERKEN

Merk	JTEKT
N° Ean13	3663952482842
Binnendiameter	25 mm
Binnendiameter	0.984" inch
Buitendiameter	47 mm
Buitendiameter	1.85" inch
Dikte	22 mm
Dikte	0.866" inch
Gewicht	167 g
Verpakking	1

[contact@123kogellager.nl](mailto:contact@123kogellager.nl)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE