

Rollager RNA4907R-JTEKT - RNA4907R-JTEKT

<https://www.123kogellager.nl/kogellager-behuizing/rollager/roll/rna4907r-jtekt>

Machined ring needle roller bearings Koyo

F_w 29 ~ 37 mm

Without inner ring



| Boundary dimensions (mm) | | | | Basic load ratings (kN) | | | Limiting speeds ¹⁾ (min ⁻¹) | | Bearing No. Without inner ring |
|--------------------------|-------|-------|-------|-------------------------|-----------------|------------------------------------|--|----------|-----------------------------------|
| F_w | d | D | B | C_r | C_{10} | Oil lub. | | | |
| 42 | 35 | 55 | 20 | 35.1 | 52.2 | 11 000 | | RNA4907R | |
| Mounting dimensions (mm) | | | | (Refer.) Mass (kg) | | (Refer.) Applicable inner ring No. | | | |
| With inner ring | | | | Without inner ring | With inner ring | | | | |
| | d_1 | D_1 | r_1 | 0.104 | 0.168 | IRM354220 | | | |
| | min. | max. | max. | | | | | | |
| | 39 | 51 | 0.6 | | | | | | |

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

PRODUCTKENMERKEN

| | |
|----------------|---------------|
| Merk | JTEKT |
| N° Ean13 | 3663952483139 |
| Binnendiameter | 42 mm |
| Buitendiameter | 55 mm |
| Dikte | 20 mm |
| Gewicht | 104 g |
| Verpakking | 1 |

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE