

Rollager NQ50-20A-JTEKT - NQ50-20A-JTEKT

<https://www.123kogellager.nl/kogellager-behuizing/rollager/roll/nq50-20a-jtekt>

Machined ring needle roller bearings ————— **Koyo**
F_W 29 ~ 37 mm

Without inner ring



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds ¹⁾ (min ⁻¹)		Bearing No.
F _w	d	D	B	C _r	C _{0r}	Oil lub.	Without inner ring	
50	—	62	20	24.8	46.0	9 400	NQ50/20A	
		Mounting dimensions (mm)			(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.	
		d _s	D _s	r _s	Without inner ring	With inner ring		
		max.	max.	max.	—	—		
		—	58	0.8	0.126	—		

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

PRODUCTKENMERKEN

Merk	JTEKT
N° Ean13	3663952483344
Binnendiameter	50 mm
Binnendiameter	1.969" inch
Buitendiameter	62 mm
Buitendiameter	2.441" inch
Dikte	20 mm
Dikte	0.787" inch
Gewicht	126 g
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE