

Rollager RNA49-48R-JTEKT - RNA49-48R-JTEKT

<https://www.123kogellager.nl/kogellager-behuizing/rollager/roll/rna49-48r-jtekt>

Machined ring needle roller bearings Koyo

F_w 29 ~ 37 mm

Without inner ring



| Boundary dimensions (mm) | | | | Basic load ratings (kN) | | | Limiting speeds ¹⁾ (min ⁻¹) | | Bearing No. Without inner ring |
|--------------------------|-------|-------|-------|-------------------------|-----------------|------------------------------------|--|-----------|-----------------------------------|
| F_w | d | D | B | C_r | C_{10} | Oil lub. | | | |
| 55 | — | 70 | 22 | — | 46.9 | 76.5 | 8 300 | RNA49/48R | |
| Mounting dimensions (mm) | | | | (Note 1) Mass (kg) | | (Note 1) Applicable inner ring No. | | | |
| With inner ring | | | | Without inner ring | With inner ring | | | | |
| | d_a | D_a | r_a | — | — | | | | |
| | max. | max. | max. | 66 | 0.6 | 0.174 | | | |

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

PRODUCTKENMERKEN

| | |
|----------------|---------------|
| Merk | JTEKT |
| N° Ean13 | 3663952483481 |
| Binnendiameter | 55 mm |
| Buitendiameter | 70 mm |
| Dikte | 22 mm |
| Gewicht | 174 g |
| Verpakking | 1 |

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE