


Rollager NA6919-JTEKT - NA6919-JTEKT

<https://www.123kogellager.nl/kogellager-behuizing/rollager/roll/na6919-jtekt>

Machined ring needle roller bearings Koyo

F_w 29 ~ 37 mm

With inner ring



| Boundary dimensions (mm) | | | | Basic load ratings (kN) | | Limiting speed ¹⁾ (min ⁻¹) | | Bearing No. | |
|--------------------------|----|-----|----|-------------------------|-----------------|---|--------------------|-------------|------------|
| F_w | d | D | B | C_r | C_{10} | Oil lub. | Without inner ring | | |
| 110 | 95 | 130 | 63 | 173.0 | 428.0 | 4 200 | — | | |
| Mounting dimensions (mm) | | | | (Refer.) Mass (kg) | | (Refer.) Applicable inner ring No. | | | |
| With inner ring | | | | Without inner ring | With inner ring | | | | |
| NA6919 | | | | 101.5 | 123.5 | 1 | 1.27 | 2.43 | IRM9511063 |

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

PRODUCTKENMERKEN

| | |
|----------------|---------------|
| Merk | JTEKT |
| N° Ean13 | 3663952484204 |
| Binnendiameter | 95 mm |
| Buitendiameter | 130 mm |
| Dikte | 63 mm |
| Gewicht | 2430 g |
| Verpakking | 1 |

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE