


## Naaldhulslager NA4903UU-JTEKT - NA4903UU-JTEKT

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/na4903uu-jtekt>

### Machined ring needle roller bearings Koyo

$F_w$  29 – 37 mm

With inner ring



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds <sup>1)</sup> (min <sup>-1</sup> )		Bearing No.
$F_w$	d	D	B	$C_r$	$C_{10}$	Oil lub.	Without inner ring	
22	17	30	13	9.4	11.8	9 100	—	
Mounting dimensions (mm)				(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.		
With inner ring				Without inner ring	With inner ring			
NA4903UU				19	28	0.3	0.040	IRM172214

[Note] 1) Limiting speeds of bearing number NA49...UU indicates the value of sealed and grease lubricated bearings.  
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

## PRODUCTKENMERKEN

Merk	JTEKT
N° Ean13	3663952485959
Binnendiameter	17 mm
Buitendiameter	30 mm
Dikte	13 mm
Gewicht	40 g
Verpakking	1

[contact@123kogellager.nl](mailto:contact@123kogellager.nl)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE