

## Naaldhulslager NQI12-16D-JTEKT - NQI12-16D-JTEKT

https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/nqi12-16d-jtekt

Machined ring needle roller bearings Koyo

$F_w$  29 ~ 37 mm

With inner ring



Boundary dimensions (mm)					Basic load ratings (kN)		Limiting speeds <sup>1)</sup> (min <sup>-1</sup> )		Bearing No.	
$F_w$	d	D	B	$B_1$	$r$ (mm)	$C_r$	$C_{10}$	Oil lub.	Without inner ring	
16	12	24	16	16	0.3	10.9	15.2	28 000	—	
Mounting dimensions (mm)					(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.			
With inner ring					Without inner ring	With inner ring				
NQI12/16D					14	22	0.3	—	0.036	—

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.  
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

## PRODUCTKENMERKEN

Merk	JTEKT
N° Ean13	3663952488974
Binnendiameter	12 mm
Binnendiameter	0.472" inch
Buitendiameter	24 mm
Buitendiameter	0.945" inch
Dikte	16 mm
Dikte	0.63" inch
Verpakking	1

[contact@123kogellager.nl](mailto:contact@123kogellager.nl)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE