


## Naaldhulslager BK0608-JTEKT - BK0608-JTEKT

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/bk0608-jtekt>

Boundary dimensions



Models shown with cage assembly

| Bearing No. | Boundary dimensions(mm) |    |   |         |        | Basic load ratings(kN) |      | Fatigue load limit(kN) | Limiting speeds(min-1) |          |
|-------------|-------------------------|----|---|---------|--------|------------------------|------|------------------------|------------------------|----------|
|             | Fw                      | D  | d | C-3(mm) | rs(mm) | Cr                     | CoCr | Cu                     | Grease lub.            | Oil lub. |
| BK0608      | 6                       | 10 | 8 | 6.4     | 0.4    | 2.34                   | 1.95 | 0.29                   | 22000                  | 33000    |

## PRODUCTKENMERKEN

|                      |               |
|----------------------|---------------|
| Merk                 | JTEKT         |
| N° Ean13             | 3616060628732 |
| Binnendiameter       | 6 mm          |
| Buitendiameter       | 10 mm         |
| Dikte                | 8 mm          |
| Grenstoerental       | 22000 rpm     |
| Dynamische belasting | 2.34 kN       |
| Statische belasting  | 1.95 kN       |
| Verpakking           | 1             |

[contact@123kogellager.nl](mailto:contact@123kogellager.nl)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE