


Naaldhulslager HK0910-JTEKT - HK0910-JTEKT

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/hk0910-jtekt>

Boundary dimensions



Metric series with cage assembly

| Bearing No. | Boundary dimensions (mm) | | | | | Basic load ratings (kN) | | Fatigue load limit (kN) | Limiting speeds (min ⁻¹) | |
|-------------|--------------------------|----|----|---------|----------------------|-------------------------|-----------------|-------------------------|--------------------------------------|----------|
| | F _w | D | d | C (min) | r _s (min) | C _r | C _{0r} | | Grease lub. | Oil lub. |
| HK0910 | 9 | 13 | 10 | — | 0,4 | 4,57 | 5,07 | 0,77 | 15000 | 30000 |

PRODUCTKENMERKEN

| | |
|----------------------|---------------|
| Merk | JTEKT |
| N° Ean13 | 3616060628831 |
| Binnendiameter | 9 mm |
| Buitendiameter | 13 mm |
| Dikte | 10 mm |
| Grenstoerental | 19000 rpm |
| Dynamische belasting | 4.57 kN |
| Statische belasting | 5.07 kN |
| Verpakking | 1 |

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE