


## Naaldhulslager HK2210-JTEKT - HK2210-JTEKT

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/hk2210-jtekt>

Boundary dimensions



Metric series with cage assembly

Bearing No.	Boundary dimensions(mm)				Basic load ratings(kN)		Fatigue load limit(kN)	Limiting speeds(min-1)		
	F <sub>or</sub>	D	d	C <sub>3</sub> (mm)	C <sub>r</sub>	C <sub>0r</sub>		Grease lub.	Oil lub.	
HK2210	22	28	10	—	1	7.06	9.49	1.45	9600	15000

## PRODUCTKENMERKEN

Merk	JTEKT
N° Ean13	3616060629234
Binnendiameter	22 mm
Binnendiameter	0.866" inch
Buitendiameter	28 mm
Buitendiameter	1.102" inch
Dikte	10 mm
Dikte	0.394" inch
Grenstoerental	9600 rpm
Dynamische belasting	7.06 kN
Statische belasting	9.49 kN
Verpakking	1

[contact@123kogellager.nl](mailto:contact@123kogellager.nl)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE