


## Naaldhulslager J-36-JTEKT - J-36-JTEKT

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/j-36-jtekt>

Boundary dimensions



Inch series, with cage assembly

| Bearing No. | Boundary dimensions(mm) |       |      |        | Basic load ratings(kN) |      | Fatigue load limit(kN) | Limiting speeds(min-1) |          |
|-------------|-------------------------|-------|------|--------|------------------------|------|------------------------|------------------------|----------|
|             | Fw                      | D     | C    | Y(max) | Cr                     | Cor  | Cu                     | Grease lub.            | Oil lub. |
| J-36        | 4.763                   | 8.733 | 9.53 | 1.02   | 2.28                   | 1.92 | 0.29                   | 25000                  | 38000    |

## PRODUCTKENMERKEN

|                      |               |
|----------------------|---------------|
| Merk                 | JTEKT         |
| N° Ean13             | 3616060629746 |
| Binnendiameter       | 4.763 mm      |
| Binnendiameter       | 3/16" inch    |
| Buitendiameter       | 8.733 mm      |
| Buitendiameter       | 11/32" inch   |
| Dikte                | 9.53 mm       |
| Dikte                | 3/8" inch     |
| Grenstoerental       | 25000 rpm     |
| Dynamische belasting | 2.28 kN       |
| Statische belasting  | 1.92 kN       |
| Verpakking           | 1             |

[contact@123kogellager.nl](mailto:contact@123kogellager.nl)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE