

Naaldhulslager HJ-283720-JTEKT - HJ-283720-JTEKT

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/hj-283720-jtekt>

Boundary dimensions




Tableau 1

| Bearing No. | Boundary dimension (mm) | | | | Used with inner ring No. | Basic load ratings (kN) | | Fatigue load limit (kN) | Limiting speeds (min-1) | |
|-------------|-------------------------|--------|-------|---------|--------------------------|-------------------------|-----|-------------------------|-------------------------|----------|
| | Fw | D | C | r3 (mm) | | Cr | C0r | | Grease Lub. | Oil Lub. |
| HJ-283720 | 44.45 | 58.738 | 31.75 | 1.52 | IR-253820 | 61.8 | 106 | 16.6 | 6400 | 9900 |

PRODUCTKENMERKEN

| | |
|----------------------|---------------|
| Merk | JTEKT |
| N° Ean13 | 3616060632685 |
| Binnendiameter | 44.45 mm |
| Buitendiameter | 58.738 mm |
| Dikte | 31.75 mm |
| Grenstoerental | 6400 rpm |
| Dynamische belasting | 61.8 kN |
| Statische belasting | 106 kN |
| Verpakking | 1 |

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE