


## Naaldkooi K25-29-13-H-JTEKT - K25-29-13-H-JTEKT

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldkooi/k25-29-13-h-jtekt>

Boundary dimensions



Basic needle roller and cage assemblies

| Bearing No. | Boundary dimensions(mm) |    |    | Basic load ratings(kN) |      | Fatigue load limit(kN) | Limiting speeds(min-1) |          |
|-------------|-------------------------|----|----|------------------------|------|------------------------|------------------------|----------|
|             | Fw                      | Ew | B  | C                      | Cz   | C                      | Grease lub.            | Oil lub. |
| K25X29X13H  | 25                      | 29 | 13 | 12.8                   | 21.1 | 3.2                    | 11000                  | 17000    |

## PRODUCTKENMERKEN

|                      |               |
|----------------------|---------------|
| Merk                 | JTEKT         |
| N° Ean13             | 3616060634153 |
| Binnendiameter       | 25 mm         |
| Buitendiameter       | 29 mm         |
| Dikte                | 13 mm         |
| Grenstoerental       | 11000 rpm     |
| Dynamische belasting | 12.8 kN       |
| Statische belasting  | 21.1 kN       |
| Verpakking           | 1             |

[contact@123kogellager.nl](mailto:contact@123kogellager.nl)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE