


Naaldhulslager BHM1720A-JTEKT - 09263-17027-JTEKT

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/09263-17027-jtekt>

Drawn cup needle roller bearings 



Boundary dimensions (mm)			Basic load ratings (kN)		Limiting speeds (min ⁻¹)	Bearing No. ²⁾
F_w	D	C	b min.	C_0	C_{10}	Caged type With open ends With closed end
17	24	20	—	19.0	21.9	7 200

Full complement type With open ends With closed end	Recommended dimensions (mm)				(Refer.) Mass (g)	
	Shaft dia. (H6) min. max.		Housing bore dia. (H7) min. max.		With open ends	With closed end
BHM1720A	16.983 ³⁾	16.994 ³⁾	23.985 ⁴⁾	24.006 ⁴⁾	27	—

PRODUCTKENMERKEN

Merk	JTEKT
N° Ean13	4549250294792
Binnendiameter	17 mm
Buitendiameter	24 mm
Dikte	20 mm
Gewicht	27 g
Verpakking	1
Standaard	Geen standaard

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE