

Kegelager

48290-48220-TIMKEN - 48290-48220-TIMKEN

<https://www.123kogellager.nl/kogellager-behuizing/rollager/kegelager/48290-48220-timken>

TAPERED ROLLER BEARINGS
SINGLE-ROW • TYPE TS

TYPE TS

| Bearing Dimensions | | | Load Ratings | | | | | | Part Number | | |
|--------------------|---------|---------|---------------------------------------|-------------------------|---------------------------------------|--------------------------------------|-----------------------|-------|-------------|-------|-------|
| Bore d | O.D. D | Width B | Dynamic ⁽¹⁾ C ₁ | Factor ⁽²⁾ e | Dynamic ⁽¹⁾ C ₂ | Factor ⁽²⁾ e ₂ | Static C ₃ | Inner | Outer | | |
| mm | mm | mm | N | | N | | N | | | | |
| 127.000 | 182.562 | 39.688 | 20000 | 0.31 | 157 | 6900 | 30300 | 1.51 | 49300 | 48290 | 48220 |
| 0.0030 | 7.1875 | 1.5025 | 60200 | | 19000 | | 8166 | | 111900 | | |

| Bearing Dimensions | | | | | | | | | | Geometry Factors | | | Bearing Weight | |
|--------------------|---------|--------------------------|--|--------------------------------------|--|--------------------------------------|-------------------------------|-------------------------------|----------------|------------------|----------------|------|----------------|------|
| Shaft | | Housing | | Cage | | | | | G ₁ | G ₂ | C ₃ | | | |
| Width B | Width C | ER. Dr. r ⁽¹⁾ | Max Shaft Fillet Radius R ⁽¹⁾ | Backing Shoulder Dia. d ₁ | Max Housing Fillet Radius r ⁽²⁾ | Backing Shoulder Dia. D ₁ | A ₁ ⁽³⁾ | A ₂ ⁽³⁾ | | | | | | |
| 39.688 | 33.336 | -5.6 | 3.5 | 135.0 | 141.8 | 3.3 | 176.8 | 198.8 | 1.8 | 3.3 | 353.0 | 51.4 | 0.1138 | 3.26 |
| 1.9000 | 1.3125 | -0.22 | 0.14 | 5.31 | 5.55 | 0.13 | 6.93 | 6.61 | 0.07 | 0.13 | | | | 7.17 |

PRODUCTKENMERKEN

| | |
|----------------|---------------|
| Merk | TIMKEN |
| N° Ean13 | 3663952137780 |
| Binnendiameter | 127 mm |
| Buitendiameter | 182.56 mm |
| Dikte | 39.69 mm |
| Verpakking | 1 |

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE