

Kogellager enkele rij 7322-BEP-SKF - 7322-BEP-SKF

<https://www.123kogellager.nl/kogellager-behuizing/kogellager/enkele-rij/7322-bep-skf>

Dimensions d'encombrement		Charges de base		Vitesses de base		Désignation
d	D	B	C	C ₀	Vitesse de référence	Vitesse limite
mm			kN		tr/min	
110	240	50	225	224	3200	7322 BEP

Technical drawing showing three views of the bearing: front view, side view, and cross-section. Dimensions include: D=240, D₁=193,5, d₂=135, f_{1,2} max 3, d=110, d₁=160,8, B=50, r_{1,2} min 1,5, r_{1,2} max 2,5, r_{1,2} min 2,5, r_{1,2} max 2,5, D_{max}=226, D_{min}=233, D_{max}=233. Coefficients de calcul: k₁ 0,5, k₂ 1,8, e 1,14, X 0,35, Y 0,87, Y₂ 0,26.

PRODUCTKENMERKEN

Merk	SKF
N° Ean13	7316576651014
Binnendiameter	110 mm
Waterdicht maken	Niet waterdicht
Kooi	Niet-metaal
Contacthoek	40 °
Buitendiameter	240 mm
Dikte	50 mm
Grenstoerental	3200 rpm
Gewicht	9710 g
Dynamische belasting	225 kN
Statische belasting	224 kN
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE