

Naaldhulslager BA1610-ZOH-IKO - BA1610-ZOH-IKO

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/ba1610-zoh-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series

Shaft dia. mm (inch)	Standard			Closed end			Mass (Ref.)			Greas retained g	
	Standard	Mass (Ref.) g	Closed end	Standard	Mass (Ref.) g	Closed end	Standard	Mass (Ref.) g	Closed end		
25.400 (1)	—	—	—	—	—	—	—	—	—	—	
Identification number: BA 1610 Z 22											
Boundary dimensions		mm(inch)		Standard mounting dimensions		mm		Ball dynamic load rating	Ball static load rating	Allowable rotational speed(*)	Assembled inner ring
F_w	D	C	d_1	Shaft dia. d	Housing bore dia. J_7	Max.	Min.	C	C_0	rpm	—
25.400	31.750	15.881	625	25.400	25.387	31.764	31.739	11 900	18 100	15 000	—

Note(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952172804
Binnendiameter	25.4 mm
Binnendiameter	1" inch
Buitendiameter	31.75 mm
Buitendiameter	1 1/4" inch
Dikte	15.88 mm
Dikte	5/8" inch
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE