


## Naaldhulslager BA1716-ZOH-IKO - BA1716-ZOH-IKO

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/ba1716-zoh-iko>

**IKO**  
**SHELL TYPE NEEDLE ROLLER BEARINGS**  
Inch Series



BA--Z BHA--Z

Shaft dia. mm (inch)	Identification number			Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g
	Standard	Mass (Ref.) g	Closed end									
<b>26.988</b> (1.062)	---	---	---	<b>BA 1716 Z</b>	37	---	---	---	---	---	---	---

Boundary dimensions			Standard mounting dimensions				Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed <sup>(*)</sup>	Assembled inner ring	
F <sub>w</sub>	D	C	Shaft dia. h <sub>8</sub>	Housing bore dia. J7	Max.	Min.					
26.988   1.062	33.338   1.313	25.40   1.000	2.8	26.988	26.975	33.352	33.327	20 000	38 900	14 000	---

Note<sup>(\*)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

### PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952172835
Binnendiameter	26.99 mm
Buitendiameter	33.34 mm
Dikte	25.4 mm
Verpakking	1

[contact@123kogellager.nl](mailto:contact@123kogellager.nl)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE