


Naaldhulslager BAM1014-IKO - BAM1014-IKO

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/bam1014-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number											
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g			
15.875 ($\frac{5}{8}$)	—	—	—	—	—	—	—	—	BAM 1014	16.2	—	—

Boundary dimensions			Standard mounting dimensions				Basic dynamic load rating	Basic static load rating	Allowable rotational speed ^(*)	Assembled inner ring	
F_w	D	C	Shaft dia. h8		Housing bore dia. J7		C	C_0	rpm		
			Max.	Min.	Max.	Min.	N	N			
15.875 $\frac{5}{8}$	20.638 $\frac{3}{4}$	22.221 $\frac{7}{8}$	1.3	15.875	15.864	20.650	20.629	10 700	17 500	25 000	IRB 714

Note^(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952172910
Binnendiameter	15.88 mm
Buitendiameter	20.64 mm
Dikte	22.22 mm
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE