

Naaldhulslager BAM1412-IKO - BAM1412-IKO

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/bam1412-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series

Shaft dia. mm (inch)	Standard			Closed end			Identification number			Grease retained Mass (Ref.) g	Mass (Ref.) g
	Standard	Mass (Ref.) g	Closed end	Standard	Mass (Ref.) g	Closed end	Standard	Mass (Ref.) g	Closed end		
22.225 (7/8)	—	—	—	—	—	—	BAM 1412	26	—	—	—

Boundary dimensions			Standard mounting dimensions				Basic dynamic load rating	Basic static load rating	Allowable rotational speed ⁽¹⁾	Assembled inner ring
F_w	D	C	B	Shaft dia. h6		Housing bore dia. J7	C	C_0	rpm	IRB 1012
			Max.	Max.	Min.	Max.	Min.	N	N	
22.225	28.575	19.05	2.8	22.225	22.212	28.587	28.566	12 800	20 400	18 000

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952173139
Binnendiameter	22.23 mm
Binnendiameter	7/8" inch
Buitendiameter	28.58 mm
Buitendiameter	1 1/8" inch
Dikte	19.05 mm
Dikte	3/4" inch
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE