

Naaldhulslager BAM1418-IKO - BAM1418-IKO

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/bam1418-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series

BAM BHAM

Shaft dia. mm (inch)	Identification number			Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained (Ref.) g	Mass (Ref.) g																																																				
	Standard	Mass (Ref.) g	Closed end																																																														
22.225 (7/8)	—	—	—	—	—	—	—	—	—	—	—	—	—																																																				
<table border="1"> <thead> <tr> <th colspan="3">Boundary dimensions</th> <th colspan="4">Standard mounting dimensions</th> <th colspan="2">Basic dynamic load rating</th> <th colspan="2">Basic static load rating</th> <th colspan="1">Allowable rotational speed⁽¹⁾</th> <th colspan="1">Assembled inner ring</th> </tr> <tr> <th>F_w</th> <th>D</th> <th>C</th> <th colspan="2">Shaft dia. h6</th> <th colspan="2">Housing bore dia. J7</th> <th>C</th> <th>C_0</th> <th>C_0</th> <th>C_0</th> <th>rpm</th> <th></th> </tr> <tr> <td></td> <td></td> <td></td> <td>Max.</td> <td>Min.</td> <td>Max.</td> <td>Min.</td> <td>N</td> <td>N</td> <td>N</td> <td>N</td> <td></td> <td></td> </tr> </thead> <tbody> <tr> <td>22.225 (7/8)</td> <td>28.575 (1 1/4)</td> <td>28.58 (1.125)</td> <td>2.8</td> <td>22.225</td> <td>22.212</td> <td>28.587</td> <td>28.566</td> <td>19 900</td> <td>35 600</td> <td>18 000</td> <td>—</td> <td>—</td> </tr> </tbody> </table>														Boundary dimensions			Standard mounting dimensions				Basic dynamic load rating		Basic static load rating		Allowable rotational speed ⁽¹⁾	Assembled inner ring	F_w	D	C	Shaft dia. h6		Housing bore dia. J7		C	C_0	C_0	C_0	rpm					Max.	Min.	Max.	Min.	N	N	N	N			22.225 (7/8)	28.575 (1 1/4)	28.58 (1.125)	2.8	22.225	22.212	28.587	28.566	19 900	35 600	18 000	—	—
Boundary dimensions			Standard mounting dimensions				Basic dynamic load rating		Basic static load rating		Allowable rotational speed ⁽¹⁾	Assembled inner ring																																																					
F_w	D	C	Shaft dia. h6		Housing bore dia. J7		C	C_0	C_0	C_0	rpm																																																						
			Max.	Min.	Max.	Min.	N	N	N	N																																																							
22.225 (7/8)	28.575 (1 1/4)	28.58 (1.125)	2.8	22.225	22.212	28.587	28.566	19 900	35 600	18 000	—	—																																																					

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952173160
Binnendiameter	22.23 mm
Buitendiameter	28.58 mm
Dikte	28.58 mm
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE