


## Naaldhulslager BAM1422-IKO - BAM1422-IKO

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/bam1422-iko>

**IKO**  
**SHELL TYPE NEEDLE ROLLER BEARINGS**  
Inch Series



Shaft dia. mm (inch)	Identification number										
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g		
22.225 (7/8)	—	—	—	—	—	—	—	<b>BAM 1422</b>	44.5	—	—

Boundary dimensions			mm(inch)	Standard mounting dimensions				mm	Basic dynamic load rating	Basic static load rating	Allowable rotational speed <sup>(1)</sup>	Assembled inner ring
$F_w$	$D$	$C$	$B$	Shaft dia. $\phi$		Housing bore dia. $J7$		$C$	$C_0$	$N$	$N$	rpm
				Max.	Min.	Max.	Min.					
22.225	28.575	34.92	2.8	22.225	22.212	28.587	28.566	24 100	45 700	18 000	IRB 1022	

Note<sup>(1)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

### PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952173177
Binnendiameter	22.23 mm
Buitendiameter	28.58 mm
Dikte	34.92 mm
Verpakking	1

[contact@123kogellager.nl](mailto:contact@123kogellager.nl)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE