


Naaldhulslager BAM710-IKO - BAM710-IKO

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/bam710-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number									
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g		
11.112 (7/16)	—	—	—	—	—	—	BAM 710	8.5	—	—
Boundary dimensions mm(inch)		Standard mounting dimensions mm				Basic dynamic load rating	Basic static load rating	Allowable rotational speed(*)	Assembled inner ring	
F_w	D	C	b_2	Shaft dia. h8	Housing bore dia. J7	C	C_0	rpm		
11.112 (7/16)	15.875 (5/8)	15.88(625)	1	11.112 Max. Min.	11.101 Max. Min.	15.885 15.867	6 020	7 550	35 000	—

Notes(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952173528
Binnendiameter	11.11 mm
Binnendiameter	7/16" inch
Buitendiameter	15.88 mm
Buitendiameter	5/8" inch
Dikte	15.88 mm
Dikte	5/8" inch
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE