

## Rollager 30224-J2-SKF - 30224-J2-SKF

<https://www.123kogellager.nl/kogellager-behuizing/rollager/roll/30224-j2-skf>

Dimensions d'encombrement			Charges de base		Vitesse de base		Désignation
d	D	T	C	C <sub>0</sub>	Vitesse de référence	Vitesse limite	* Roulement SKF Explorer
mm			kN		tr/min		
120	215	43,5	341	465	2200	3000	30224 J2

  

The technical drawing shows a cross-section of the bearing with the following dimensions: d = 120 mm, D = 215 mm, T = 43.5 mm, B = 48 mm, d<sub>1</sub> = 161 mm, d<sub>2</sub> = 161 mm, r = 3 mm, r<sub>1</sub> = 3.5 mm, r<sub>2</sub> = 4 mm, r<sub>3</sub> = 4 mm, r<sub>4</sub> = 4 mm, r<sub>5</sub> = 4 mm, r<sub>6</sub> = 4 mm, r<sub>7</sub> = 4 mm, r<sub>8</sub> = 4 mm, r<sub>9</sub> = 4 mm, r<sub>10</sub> = 4 mm, r<sub>11</sub> = 4 mm, r<sub>12</sub> = 4 mm, r<sub>13</sub> = 4 mm, r<sub>14</sub> = 4 mm, r<sub>15</sub> = 4 mm, r<sub>16</sub> = 4 mm, r<sub>17</sub> = 4 mm, r<sub>18</sub> = 4 mm, r<sub>19</sub> = 4 mm, r<sub>20</sub> = 4 mm, r<sub>21</sub> = 4 mm, r<sub>22</sub> = 4 mm, r<sub>23</sub> = 4 mm, r<sub>24</sub> = 4 mm, r<sub>25</sub> = 4 mm, r<sub>26</sub> = 4 mm, r<sub>27</sub> = 4 mm, r<sub>28</sub> = 4 mm, r<sub>29</sub> = 4 mm, r<sub>30</sub> = 4 mm, r<sub>31</sub> = 4 mm, r<sub>32</sub> = 4 mm, r<sub>33</sub> = 4 mm, r<sub>34</sub> = 4 mm, r<sub>35</sub> = 4 mm, r<sub>36</sub> = 4 mm, r<sub>37</sub> = 4 mm, r<sub>38</sub> = 4 mm, r<sub>39</sub> = 4 mm, r<sub>40</sub> = 4 mm, r<sub>41</sub> = 4 mm, r<sub>42</sub> = 4 mm, r<sub>43</sub> = 4 mm, r<sub>44</sub> = 4 mm, r<sub>45</sub> = 4 mm, r<sub>46</sub> = 4 mm, r<sub>47</sub> = 4 mm, r<sub>48</sub> = 4 mm, r<sub>49</sub> = 4 mm, r<sub>50</sub> = 4 mm, r<sub>51</sub> = 4 mm, r<sub>52</sub> = 4 mm, r<sub>53</sub> = 4 mm, r<sub>54</sub> = 4 mm, r<sub>55</sub> = 4 mm, r<sub>56</sub> = 4 mm, r<sub>57</sub> = 4 mm, r<sub>58</sub> = 4 mm, r<sub>59</sub> = 4 mm, r<sub>60</sub> = 4 mm, r<sub>61</sub> = 4 mm, r<sub>62</sub> = 4 mm, r<sub>63</sub> = 4 mm, r<sub>64</sub> = 4 mm, r<sub>65</sub> = 4 mm, r<sub>66</sub> = 4 mm, r<sub>67</sub> = 4 mm, r<sub>68</sub> = 4 mm, r<sub>69</sub> = 4 mm, r<sub>70</sub> = 4 mm, r<sub>71</sub> = 4 mm, r<sub>72</sub> = 4 mm, r<sub>73</sub> = 4 mm, r<sub>74</sub> = 4 mm, r<sub>75</sub> = 4 mm, r<sub>76</sub> = 4 mm, r<sub>77</sub> = 4 mm, r<sub>78</sub> = 4 mm, r<sub>79</sub> = 4 mm, r<sub>80</sub> = 4 mm, r<sub>81</sub> = 4 mm, r<sub>82</sub> = 4 mm, r<sub>83</sub> = 4 mm, r<sub>84</sub> = 4 mm, r<sub>85</sub> = 4 mm, r<sub>86</sub> = 4 mm, r<sub>87</sub> = 4 mm, r<sub>88</sub> = 4 mm, r<sub>89</sub> = 4 mm, r<sub>90</sub> = 4 mm, r<sub>91</sub> = 4 mm, r<sub>92</sub> = 4 mm, r<sub>93</sub> = 4 mm, r<sub>94</sub> = 4 mm, r<sub>95</sub> = 4 mm, r<sub>96</sub> = 4 mm, r<sub>97</sub> = 4 mm, r<sub>98</sub> = 4 mm, r<sub>99</sub> = 4 mm, r<sub>100</sub> = 4 mm.

Coefficients de calcul  
 $\alpha = 0,43$   
 $\gamma = 1,4$   
 $\beta = 0,8$

### PRODUCTKENMERKEN

Merk	SKF
N° Ean13	3616060106964
Binnendiameter	120 mm
Buitendiameter	215 mm
Dikte	43.5 mm
Gewicht	6130 g
Verpakking	-

[contact@123kogellager.nl](mailto:contact@123kogellager.nl)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE