


Naaldhulslager BA4410-ZOH-IKO - BA4410-ZOH-IKO

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/ba4410-zoh-iko>



IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series

BA--Z BHA--Z

Shaft dia. mm (inch)	Identification number			Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained (Ref.) g	Mass (Ref.) g
	Standard	Mass (Ref.) g	Closed end										
69.850 (2 3/4)	--	--	--	BA 4410 Z	85.5	--	--	--	--	--	--	--	--

Boundary dimensions			Standard mounting dimensions				Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽¹⁾ rpm	Assembled inner ring	
F _w	D	C	Shaft dia. H7	Housing bore dia. J7	Max.	Min.					
69.850 (2 3/4)	79.375 (3 1/8)	15.88 (5/8)	2.8	69.850	69.831	79.393	79.383	25 000	50 800	3 500	--

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952049977
Binnendiameter	69.85 mm
Buitendiameter	79.38 mm
Dikte	15.88 mm
Gewicht	88 g
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE