

Rollager NCF2940CV-SKF - NCF2940CV-SKF

<https://www.123kogellager.nl/kogellager-behuizing/rollager/roll/ncf2940cv-skf>

Dimensions d'encadrement			Charges de base		Vitesses de base		Désignation
d	D	B	dynamique C	statique C ₀	Vitesse de référence tr/min	Vitesse limite	
200	280	48	528	965	1000	1300	NCF 2940 CV

The technical drawing shows the bearing's geometry with the following dimensions: $d = 200$, $D = 280$, $B = 48$, $r_{1,2max} = 2,1$, $r_{max} = 2$, $D_{max} = 269$, $D_{min} = 211$, $D_{topmax} = 268$, $D_{topmin} = 212$, $r_{max} = 2$. Coefficients of calculation are listed as $k_1 = 0,2$, $k_2 = 0,3$, and $Y = 0,4$.

PRODUCTKENMERKEN

Merk	SKF
N° Ean13	7316572343302
Binnendiameter	200 mm
Buitendiameter	280 mm
Dikte	48 mm
Grenstoerental	1300 rpm
Gewicht	9110 g
Dynamische belasting	528 kN
Statische belasting	965 kN
Verpakking	1
Standaard	Geen standaard

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE